

DRUM EQUIPMENT

FORK MOUNTED DRUM LIFTERS

- Allows operator to raise, transport, tip and drain loaded drums without leaving their seat
- Geared design with pull chain or battery powered with pendant for controlled dispensing of open and closed head steel drums up to 2000 lbs.
- Manipulation of pull chain on geared type models for 360° rotation
- Attaches easily to truck by sliding onto forks and tightening screw locks
- No electrical or hydraulic connections to truck are needed
- 6-1/2" W x 26-5/8" D x 2-1/2" H fork pockets; inside width between forks must be 25"
- Options are available to handle plastic, fibre, and steel drums
- 22 1/2" diameter

Model No.	Mfg No.	Drum Size Gallons	Tilt Type	Full Drum Cap. lbs.	Half Drum Cap. lbs.	Wt. lbs.	Price /Each
DA133	285A	45 Imp. /55 US ¹	Geared	800	500	149	
DA135	285A-HD	45 Imp. /55 US	Geared	1500	800	171	
DA134	285A-GR	45 Imp. /55 US	Geared	2000	1000	273	

Note: Battery powered option available



DA133

Controlled pouring up to 2000 lbs.



DRUM LIFTERS

Safely transport, position and drain open and closed head steel drums. Simply attach the lifter on hook of chain block, monorail or crane, cinch saddle around drum, and then raise to the required height and position. Ratchet mechanism securely tightens saddle to drum. Choice of manual or geared models.

MANUAL TILT

- Ideal for low level pouring and dumping operations
- 800 lbs. full drum capacity, 500 lbs. half drum capacity
- Tilt lock on each side of hanger frame is used to secure drum in a vertical or horizontal position

Model No.	Mfg No.	Drum Size	Price/Each
DA199	85A	45 imp. gal./55 US gal. steel; 22 1/2" dia.	
DA200	85I & 55/30-19	25 and 45 imp. gal./55 US gal. steel; 18 1/2" - 19" and 22 1/2" dia. Includes DC280	
DA201	85C	21" - 23" dia. fibre or steel	

Note: Options and accessories are available



DA199

GEARED TILT

- Accurate pouring from any height
- Handles drums up to 2000 lbs full drum capacity
- Rotation of drum is controlled by 12' chain loop
- Optional MORStop™ tilt brake holds drum tilt position constant even when tension from the pull chain is removed



Model No.	Mfg No.	Drum Size	Full Drum Cap. lbs.	Half Full Cap. lbs.	Wt. lbs.	Price /Each
DA121*	185A	45 imp. gal./55 US gal. steel; 22" - 23 1/2" dia.	800	500	98	
DA124*	185A-HD	45 imp. gal./55 US gal. steel; 22 1/2" dia.	1500	800	114	
DA123**	185A-GR	45 imp. gal./55 US gal.; 22 1/2" dia.	2000	1000	206	

OPTION

DC077	3900-P	MORStop™ Tilt Brake Option
-------	--------	----------------------------

* Chains can be guided into locking slots to hold the drum's position, allowing the operator to let go

**Worm gear speed reducer on DA123 tends to let drum stay where it is stopped, removing the need for the optional tilt brake



DA124



DRUM CONES

- Used to dispense dry materials
- Replaces drum lids with a cone and clamp collar to reduce dust and keep material clean
- Clamp collar is included
- Start and stop dispensing with a slide gate or iris valve
- Slide gate and iris valve openings are 6"
- To be used on fibre or steel drums with a 15 1/2" to 23 1/2" diameter
- Cone opening has a 45° angle and is made of regular steel
- Also available in stainless steel and other sizes

DC276



DC277



Model No.	Opening	Outside Rim Dia"	Wt. lbs.	Price /Each
DC276	Slide Gate	23 3/8	50	
DC277	Iris Valve	23 3/8	50	